

# ADHESIVE COVERAGE RATES

		BEAD SPACING		NOTES		
		12 INCHES O.C.	6 INCHES O.C.			
<b>DURO-GRIP PRODUCTS</b>						
Insta-Stik		800 sq. ft.	400 sq. ft.	Order 1 wand kit per every 3 tanks		
<b>ICP Adhesives</b>		Board-Max	CR-20	Board-Max	CR-20	1 hose kit included per tank set
	To concrete	3,000 sq. ft.	2,000 sq. ft.	1,500 sq. ft.	1,000 sq. ft.	
	To insulation	3,000 sq. ft.	2,000 sq. ft.	1,500 sq. ft.	1,000 sq. ft.	
	To smooth BUR	2,600 sq. ft.	1,600 sq. ft.	1,300 sq. ft.	800 sq. ft.	
	To modified bitumen	2,600 sq. ft.	1,600 sq. ft.	1,300 sq. ft.	800 sq. ft.	
	To gypsum	2,600 sq. ft.	1,600 sq. ft.	1,300 sq. ft.	800 sq. ft.	
	To lightweight concrete	2,600 sq. ft.	1,600 sq. ft.	1,300 sq. ft.	800 sq. ft.	
	To wood	2,600 sq. ft.	2,000 sq. ft.	1,300 sq. ft.	1,000 sq. ft.	
	To cementitious wood fiber (Tectum)	2,200 sq. ft.	1,200 sq. ft.	1,100 sq. ft.	600 sq. ft.	
	To steel	N/A	N/A	1,500 sq. ft.	1,000 sq. ft.	
<b>OlyBond 500 (Bag in Box)</b>						Requires OMG PaceCart
	To concrete	2,000 sq. ft.		1,000 sq. ft.		
	To insulation	2,000 sq. ft.		1,000 sq. ft.		
	To smooth BUR	1,600 sq. ft.		800 sq. ft.		
	To modified bitumen	1,600 sq. ft.		800 sq. ft.		
	To gypsum	1,000 sq. ft.		500 sq. ft.		
	To lightweight concrete	1,500 sq. ft.		750 sq. ft.		
	To wood	2,000 sq. ft.		1,000 sq. ft.		
	To steel	N/A		1,000 sq. ft.		
<b>OlyBond 500 (SpotShot, 4/case)</b>		400 – 600 sq. ft.		200 – 300 sq. ft.		Requires SpotShot Applicator
<b>Millenium PG-1</b>		See OlyBond 500 (Bag in Box) above				Requires Cyclone Applicator
<b>Millenium One Step</b>		See OlyBond 500 (SpotShot, 4/case) above				
<b>BAREBACK MEMBRANE PRODUCTS</b>						
<b>WB II</b>	One-sided application	700 – 900 sq. ft. (900 sq. ft. for primed surfaces)				Use 9-inch medium nap roller
<b>SB IV</b>	Two-sided application	300 sq. ft.				Use 9-inch medium nap roller
<b>Solvent-Grip</b>	Two-sided application	400 sq. ft.				Requires hose, spray gun and 2-foot extension
<b>FLEECE MEMBRANE PRODUCTS</b>						
<b>CR-20</b>	Spatter method	2,000 sq. ft. (2,000 – 2,200 sq. ft. for primed surfaces)				1 hose kit included per tank set
<b>WB II</b>	One-sided application	500 sq. ft.				Use 9-inch medium nap roller
<b>Duro-Fleece OMG (Bag in Box)</b>						Requires OMG PaceCart
	To concrete	2,000 sq. ft.		1,000 sq. ft.		
	To insulation	2,000 sq. ft.		1,000 sq. ft.		
	To smooth BUR	1,600 sq. ft.		800 sq. ft.		
	To modified bitumen	1,600 sq. ft.		800 sq. ft.		
	To gypsum	1,000 sq. ft.		500 sq. ft.		
	To lightweight concrete	1,500 sq. ft.		750 sq. ft.		
	To wood	2,000 sq. ft.		1,000 sq. ft.		
<b>Duro-Fleece OMG (SpotShot, 4-Case)</b>		400 – 600 sq. ft.		200 – 300 sq. ft.		Requires SpotShot Applicator
<b>OTHER PRODUCTS</b>						
<b>SureBond 240 (trowelable mastic)</b>	One-sided application	450 sq. ft.				Requires trowel