

DURO-LAST[®] PITCH PAN FILLER

DESCRIPTION:


Duro-Last[®] Pitch-Pan Filler is an easy flowing, self-leveling sealant for use in pitch-pans. The sealant is UV and impact resistant, and is formulated for adhesion to most types of building materials. Care must be taken since Pitch Pan Filler does not adhere to Kynar[®]-coated metal and asphalt materials. The high tack ensures a weather-tight seal around penetrations. It is excellent for use in areas subjected to stress and vibration as well as to expansion and contraction.

INSTALLATION:

1. Read the MSDS for the product prior to use.
2. Duro-Last prefabricated vinyl-coated metal pitch pans are recommended.
3. Pitch-pans must be constructed of sheet metal, wood, PVC pipe or similar, rigid, construction material.
4. If a Duro-Last prefabricated vinyl-coated metal pitch-pan is not being used, a membrane flashing must be used to flash the pitch-pan. Rectangular flashings must be terminated with termination bar or extended into the pitch-pan. Round flashings may be terminated using stainless steel bands or extended into the pitch-pan.
5. The pitch-pan must be clean and dry prior to adding filler material.
6. The bulk of the pitch-pan can be filled with material such as mortar, concrete or insulation. If there are voids in the fill material, take precaution to prevent the Pitch Pan Filler from migrating through the fill material.
7. A minimum depth of ½ inch of sealant is required.
8. See detail drawings 4030, 4040 and 4045.
9. Use mineral spirits for cleanup.

NOTE:

- This product is only intended for pitch pan applications.

Duro-Last Pitch Pan Filler		
	Item #	1122
	Packaging	10.1 fl. oz. cartridge (30 per case)
	Volume	Approximately 18 cubic inches
	Texture	Smooth
	Color	Gray
	Application Temperature Range	0 – 120° F
	Skin Time	20 – 45 minutes
	Cure Time	48 – 72 hours
	Odor	Mild
	Solubility	Insoluble in water. Soluble in most organic solvents.
Shelf Life	12 months, unopened. Store below 80° F.	