


DURO-LIGHT™ CURB MOUNT SKYLIGHT


DESCRIPTION:

Duro-Light™ skylights offer outstanding lighting and thermal performance in a versatile range of dome or pyramid styles. These skylights offer the highest performance in a fixed-unit, plastic-glazed skylight.

MODELS CS AND CSP:

- For use on 1-1/2" thick site-built or prefabricated curbs.
- Fully assembled with corrosion-proof screws and high-performance weather seals.
- Integral condensation gutter and counter-flashing downward leg.
- Aluminum-extruded, heliarc-welded retainer frame.
- Glazing is available in thermoformed acrylic and polycarbonate single, double or triple domes.





UNIT SKYLIGHT OPTIONS

Hurricane Resistant (HR) Glazing	 Provided with co-polyester to meet test requirements: ASTM-1886, ASTM-1996, TAS 201, 202 and 203. 			
	 Hurricane unit model 5296 or smaller can achieve a 75DP rating. Units larger than model 5276 can achieve a 50DP rating. 			
	Available in clear or white glazing.			
Blast Resistant (BR) Glazing	Provided with co-polyester to meet test requirements: ASTM–F1642–04, GSA-TS01-2003.			
	Available in clear or white glazing.			
Pyramid Dome (P)	Available in curb mount and deck mount.			
Aerogel	Available in curb mount and deck mount.			
Thermalized Sentinel Fall Protection	Tested to compliance with AAMA\WDMA\CSA\101\I.S.2\A440 as required by the International Building Code.			
	• Tested, when new, to 800 ftlb. to comply with the intent of OSHA fall protection regulation 29 CFR 1910.23 (e)(8)*, Cal-OSHA Title 8, Chapter 4, Section 3212 (e)(2).			
	Provided with impact modified acrylic double domes or pyramids depending on size required.			
	Offered in Clear/Clear, Clear/White or Bronze/Clear color combinations.			

DURO-LIGHT™ CURB MOUNT SKYLIGHT

STANDARD SIZES AND AVAILABLE OPTIONS

Outside Dimensions of Curb	Pyramid Dome	Aerogel	Hurricane Resistant	Blast Resistant
22" x 22"	Х	Х	х	х
25 ¼" x 25 ¼"	Х	Х	Х	Х
33 ¼" x 33 ¼"	Х	Х	Х	Х
40" x 40"	Х	Х	х	Х
49 ¼" x 49 ¼"	Х	Х	х	Х
58" x 58"	Х	Х		
71" x 71"	Х	Х		
78" x 78"	Х	Х		
95 ½" x 95 ½"	Х	Х		
25 ¼" x 33 ¼"	Х	Х	х	Х
25 ¼" x 49 ¼"	Х	Х	х	Х
33 ¼" x 49 ¼"	Х	Х	х	Х
33 ¼" x 72 ½"	Х	Х	X	Х
40" x 78"	Х	Х	Х	х
49 ¼" x 72 ½"	Х	Х	Х	Х
49 ¼" x 92 ½"	Х	Х	Х	
60 ½" x 72 ½"	Х	Х		

SAFETY CONSIDERATIONS

- Although the skylights are designed to protect against accidental falls, they should never be walked upon under any circumstances. The owner or contractor should restrict access only to authorized personnel who have been adequately cautioned as to the location of the skylights.
- The use of skylight guards is strongly recommended.