



Snap-On Fascia Base

Description:

The Fascia Base functions as a cleat to be used with the 2-Piece Snap-On Cover. Fascia Base may be used on eaves to allow water to flow over the roof edge termination.

- Fabricated in 10' lengths and 3" 8" widths.
- Used with 2-Piece Snap-On Compression Cover.
- Manufactured from 24-gauge Galvalume[®] and 24-gauge stainless steel.

Energy Efficiency:

LEED® and ENERGY STAR® compliant.

Installation:

- 1. A wood nailer is required if 1" or greater of insulation is used.
- 2. This nailer should be attached to the wall in accordance with ANSI/SPRI ES-1 3.9.
- Install in accordance with EXCEPTIONAL® Metals Detail #3560.
- Any deviation from the requirements set forth in detail drawings must be pre-approved, in writing, by the EXCEPTIONAL Metals Technical Department.

Codes and Standards:

 ANSI/SPRI ES-1 Compliant for 4", 6" and 8" base.

Warranty:

EXCEPTIONAL Metals offers a finish and substrate warranty. Contact the membrane manufacturer for any additional warranty that may be offered.


Technical Services:


Product samples, detail sheets, color chips, and color chart are available for your submittal package. For assistance with questions or submittals, contact your local representative or call EXCEPTIONAL Metals.





Fascia Base shown with 2-Piece Snap-On Compression Cover. -See 2-Piece Snap-On Compression Cover PDS for material gauge and finishes.





[&]quot;"Duro-Last" and "EXCEPTIONAL" are registered marks owned by Duro-Last Roofing, Inc. "Galvalume" is a registered mark owned by BIEC International Inc. "LEED" is a trademark owned by the U.S. Green Building Council and is used with permission. "ENERGY STAR" is a registered mark owned by the U.S. Government. ENERGY STAR is only realid in the United States.

Revised 10/02/2017