

# RhinoBond® Plate

## PRODUCT DATA SPECIFICATIONS

### PRODUCT DESCRIPTION

OMG RhinoBond Plates are designed to secure roof insulation and thermoplastic\* roof membranes. Plates are 3 inches (80mm) round, specially coated Galvalume, installed with OMG-manufactured fasteners\*\* on steel, wood or structural concrete roof decks.

All RhinoBond plates have a recessed center and a raised flat bonding surface, and come in easy to handle weather-resistant packaging.

**TPO:** RhinoBond Plates for TPO membranes are gold.

**PVC:** RhinoBond Plates for PVC membranes are black.

### FEATURES & BENEFITS

- RhinoBond is a Factory Mutual approved system. See specific manufacturers for FM approvals.
- RhinoBond Plates meet FM 4470 criteria for corrosion resistance, and feature a wide welding surface to promote a strong bond.
- RhinoBond Plates are packaged in weather-resistant pails for easy handling.

### APPLICATION

RhinoBond is a proprietary roof attachment system approved for use by select roofing manufacturers. The system requires the use of RhinoBond Plates and OMG manufactured fasteners, as well as a RhinoBond welding tool. Pre-drilling is required on structural concrete decks.

The RhinoBond System is compatible with polyisocyanurate and hard cover board, as well as any insulation that will not melt by the induction welding process. Induction welding should not be used on extruded polystyrene, EPS or foil-fasted insulation boards.

Pull tests should always be conducted to determine proper fastener selection.

### PACKAGING

RhinoBond Plates are packaged in plastic weather-resistant pails of 500 pieces each.

### APPROVALS



**Factory Mutual listings refer to this product as RhinoBond Insulation Plate (PVC, TPO).**

\*For use with approved PVC and TPO membranes only.

\*\*Consult roofing manufacturer for specific system ratings and requirements.

TPO



PVC

USE WITH  
**S**  
**W**  
**SC**  
DECK TYPES

### PHYSICAL DATA†

The data below is constant for each OMG RhinoBond Plate.

SIZE	MATERIAL
3" (80mm) round	Coated Galvalume

### ORDERING INFORMATION

CAT. NO.	MEMBRANE	PKG	WEIGHT LBS (KG)
RBP80A-TPO	TPO	500	35 (15.89)
RBP80B-PVC	PVC	500	35 (15.89)

†All sizes are nominal.



#### KEY:

<b>S</b> Steel	<b>SC</b> Structural Concrete
<b>W</b> Wood	<b>LC</b> Lightweight Concrete
<b>G</b> Gypsum	<b>LWIC</b> Lightweight Insulating Concrete
<b>P</b> Purlins	<b>CWF</b> Cementitious Wood Fiber



## ROOFING PRODUCTS

153 BOWLES ROAD, AGAWAM, MA 01001 USA

800-633-3800 413-789-0252 [OMGROOFING.COM](http://OMGROOFING.COM)

RhinoBond® is protected under U.S. Patent Nos. 6,710,314; 6,849,837; 7,399,949; 8,492,683; 8,933,379. Canadian Patent Nos. 2,458,353; 2,602,753. U.S. Patent Pending. RhinoBond® is a registered trademark of OMG, Inc. Copyright © 2015 OMG, Inc. All rights reserved.

Superior productivity.  
Superior performance.

